

CorkDirect floating floor plank technical specifications

Description	Tongue and groove floating floor planks for commercial and residential applications.
Size	36" x 12" x 1/2"
Composition and Density	Composite cork surface layer: 4 mm, density 28 lb/ft ³ Interlocking MDF layer: 6 mm (1/4"), density 45 lb/ft ³ Cork underlayment layer: 2 mm, density 13 lb/ft ³
Finish	UV-cured acrylic, no organic solvents, no VOCs.
Shock Absorption	[UNE 56 817 74] Initial maximum indentation < 0.19 mm Maximum indentation after 1 hour < 0.08 mm
Indentation	[ISO 3810 1987] Initial indentation < 1.7 % Residual indentation < 0 %
Formaldehyde	Interlocking MDF layer: DCO Class E1 < 9 mg. per 100 g.
Flammability	Average critical radiant flux 0.60 w/cm ² (unfinished)
Packaging	6 planks per pack - 18 sq. ft. 60 packs per pallet or 1080 sq. ft.
Storage	Store horizontally.
Installation	Glueless, self-locking planks. See instructions.
Acoustical Ratings	8" Concrete slab: STC 58db IIC 68db NC 30db . . .with drop ceiling: STC 60db IIC 73db NC 30db
Additional information	techinfo@corkdirect.com (800) 344-CORK (2675)